



ACO Specification Information

**Key**

- ① Overall dimension at bottom of plinth
- ② Clear working dimension at plinth opening
- ③ Overall dimension at top of plinth

**Cable pit and riser**

Description	Part No	SEEPL code	Internal clear opening L x W x D (mm)	Total product weight (kg)	Individual lid lifting weight (kg)
P6 - plastic pit	75475		1268 x 455 x 616	33	
P8 - plastic pit	75019		1268 x 455 x 836	42	
PlinthP6/8 - concrete plinth	142236		1250 x 440 x 150	325	
P6/8 - steel lid (Class B)	142241	PlinthP6-8-142241		44	21 (max)
P6/8 - steel lid (Class D)	142851	PlinthP6-8-142851		66	32 (max)

**Accessories & ancillary items**

Description	Part No	Weight kg
Lid Lifting Tool	<b>142232</b>	0.5
Pit expansion tool	<b>142233</b>	4
ID Plates	<b>On Enquiry</b>	N/A
Route Marker Plates	<b>On Enquiry</b>	N/A
SCEC (SL3) Padlocks	<b>On Enquiry</b>	0.5
Swing Arm	<b>On Enquiry</b>	1

**Specifications**

**General**

The cable pit shall be ACO PlinthP6 PITLOK® SCEC (SL1) - concrete plinth with Class B 80kN / D240kN (AS 3996) steel lids as supplied by ACO Pty Ltd or equal approved.

The plinth and lid system is fully tested and assessed on behalf of SCEC. SCEC have subsequently endorsed the plinth & lid system contingent on the use of SCEC (SL3) padlocks to secure the lids

**Materials**

The plinth shall be manufactured from steel reinforced cement concrete with:

Compressive strength: 40MPa

The nominal clear opening shall be 1,250mm x 440mm.

**Lid**

The lid shall be a SCEC (SL1) approved tamper evident locking steel lid. All lids must be load certified to AS 3996 and NATA test certificates must be supplied.

**Pit**

This plinth and lid system is designed for use with the P6 and P8 plastic pit - see separate Spec Info for pit details

**Installation**

The cable pit shall be installed in accordance with the manufacturer's installation instructions and recommendations.

\* delete as applicable

**ACO Limited**  
**New Zealand**  
 Ph: 0800 448 080  
 www.aconz.co.nz  
 sales@aconz.co.nz



© September 2022 ACO Limited. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Limited. pursues a policy of continuous product development and reserves the right to amend specifications without notice.