
S100K/H100SK Iron Slotted grate

Product Features

G

Certified to AS 3996 Load Class G (900kN) (NATA endorsed load test reports available)



AS 3996 (Clause 3.3.6) compliant for bicycle tyre penetration resistance

- Recesses in grate fit around 'anti-shunt' lugs on the edge rail to prevent longitudinal movement
- PowerLok barless and boltless locking system
- Suitable for use with S100K, H100SK channels
- Manufactured from ductile iron to AS 1831 Grade 500-7



Specifications

The grate shall be ACO S100K/H100SK* Iron Slotted grate with **PowerLok** barless and boltless locking system as manufactured by ACO. This grate has an overall width of 138mm and overall length of 500mm. Slot widths measure at a maximum of 12mm.

Materials & Design

The grate shall be manufactured from ductile iron and have minimum properties and characteristics as follows:

- · Recesses in grate fit around 'anti-shunt' lugs on the edge rail to prevent longitudinal movement
- Manufactured from ductile iron to AS 1831 Grade 500-7
- Certified to AS 3996 Load Class G (900kN)¹
- Meets AS 1428.2 (Clause 9c); AS 3996 (Clause 3.3.6)
- Intake area of 17,420mm² per half metre of grate

¹ NATA endorsed test reports available


For the specification of the ACO Drain channel system selected, click: http://www.acodrain.com.au/resources

*delete as appropriate



ACO DRAIN®

S100K/H100SK Iron Slotted grate



Description	Part No.	Length (mm)	Width (mm)	Weight (kg)
PowerLok grate S100K/H100SK Iron Slotted Grate removal tool PowerLok safety clip	96082 01318 10443	500 - -	138 - -	5.6 0.1

PowerLok locking mechanism					
	- PowerLok Grate - Lug - Lug PowerLok Device 'unlocked' position	ACO PowerLok is a patented barless and boltless locking system, grates are removed and replaced with the minimum time and effort for ease of maintenance.			
	- PowerLok Rail	Lugs on the rail opposite the PowerLok device slots into recesses in the grate, the PowerLok			
	PowerLok Device 'locked' position - Recess in Grate - PowerLok Rail	device is used to engage the lug on the rail at two locations per grate to 'lock' the grate to the channel.			

ACO Polycrete Pty Ltd Australia

Ph: 1300 765 226 www.acodrain.com.au sales@acoaus.com.au



Ph: 0800 448 080 www.acodrain.co.nz sales@aconz.co.nz

SPEC

<u>E</u> M

© February, 2017 ACO Polycrete Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Polycrete Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.