



This grate is part of ACO's Heelsafe® Anti-Slip range. For more information visit [www.heelsafe.com.au](http://www.heelsafe.com.au)

**Product Features**

-  Certified to EN 1433 Load Class C 250 (kN) which is similar to AS 3996 Load Class D (210kN) (NATA endorsed load test reports available)
-  AS 3996 (Clause 3.3.5) compliant for surface openings in pedestrian areas  
ASME A112.6.3 (Section 7.12) compliant - American high heel standard
-  AS 4586: P5 – Slip resistance classification for Wet Pendulum Test  
AS 4586: C/C<sup>1</sup> – Slip resistance classification for Wet-Barefoot Inclining Platform Test  
AS 4586: R12/R13<sup>1</sup> - Slip resistance classification for Oil-Wet Inclining Platform Test
-  AS 1428.2 (Clause 9c) compliant for wheelchair and walking cane safety
-  AS 3996 (Clause 3.3.6) compliant for bicycle tyre penetration resistance
- Raised microgrip pattern on top of nodes for slip resistance
- Corrosion resistant
- **DrainLok** barless and boltless locking system
- Suitable for use with K100, KS100, H100K, H100KS channels
- Manufactured from polyamide

<sup>1</sup>. Test direction (perpendicular/parallel) relative to the grate's length (NATA endorsed test reports available)



**Specifications**

The grate shall be ACO Type 492D Plastic Slotted Heelsafe® Anti-Slip grate with DrainLok barless and boltless locking system as manufactured by ACO. This grate has an overall width of 123mm and overall length of 500mm. Slot widths measure at a maximum of 8mm.

**Materials & Design**

The grate shall be manufactured from polyamide and have **minimum** properties and characteristics as follows:

- Raised microgrip pattern on top of nodes for slip resistance
- Corrosion resistant
- Manufactured from polyamide
- Certified to EN 1433 Load Class C 250 (kN)<sup>2</sup> which is similar to AS 3996 Load Class D (210kN)
- AS 4586: P5 – Slip resistance classification for Wet Pendulum Test<sup>2</sup>
- AS 4586: C/C<sup>1</sup> – Slip resistance classification for Wet-Barefoot Inclining Platform Test<sup>2</sup>
- AS 4586: R12/R13<sup>1</sup> – Slip resistance classification for Oil-Wet Inclining Platform Test<sup>2</sup>
- Meets AS 1428.2 (Clause 9c); AS 3996 (Clause 3.3.5 & 3.3.6); ASME A112.6.3 (Section 7.12)
- Intake area of 14,310mm<sup>2</sup> per half metre of grate

<sup>1</sup> Test direction (perpendicular/parallel) relative to the grate's length

<sup>2</sup> NATA endorsed test reports available


For the specification of the ACO Drain channel system selected, click: <http://www.acodrain.com.au/resources>

**ACO DRAIN®**


**Type 492Q Plastic Slotted Heelsafe® Anti-Slip grate**



**Plan view**




**Side elevation**



Description	Part No.	Length (mm)	Width (mm)	Weight (kg)
<b>DrainLok grate</b>				
Type 492D Plastic Slotted Heelsafe® Anti-Slip	<b>132720</b>	500	123	1.0
Grate removal tool	<b>01318</b>	-	-	0.1

**'DrainLok' locking mechanism**



ACO **DrainLok™** is a patented, boltless locking system that removes the need for bolts and bars and improves the hydraulic capacity of the channel. The **DrainLok™** mechanism simply clips into the channel edge rail for rapid installation. ACO **DrainLok™** grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.

**ACO Pty Ltd**  
Australia  
Ph: 1300 765 226  
www.acodrain.com.au  
sales@acoaus.com.au

**ACO Limited**  
New Zealand  
Ph: 0800 448 080  
www.acodrain.co.nz  
sales@aconz.co.nz



© April 2018 ACO Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Polycrete Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.