





**Cable pit - full body**



**Cable pit - split body**



**Key**

- ① Clear working dimension at pit base
- ② Clear working dimension at pit opening
- ③ Clear working dimension beneath lid rebate

## ACO CABLEMATE

# J8P - ACO PITLOK® SCEC (SL1) - concrete pit & steel lid

### Cable pit and riser

Description	Part No	Depth mm	Weight kg
J8P - ACO PitLok® - concrete pit & steel lid - full body	<b>142247</b>	1,070	862
J8P - ACO PitLok® - concrete pit & steel lid - split body	<b>142248</b>	1,070	862

### Accessories & ancillary items

Description	Part No	Weight kg
Lid Lifting Tool	<b>142232</b>	0.5
ID Plates	<b>On Enquiry</b>	N/A
Route Marker Plates	<b>On Enquiry</b>	N/A
SCEC (SL3) Padlocks	<b>On Enquiry</b>	0.5
Swing Arm	<b>On Enquiry</b>	1
SCEC (SL1) approved precast concrete riser	<b>On Enquiry</b>	Variable

### Specifications

#### General

The cable pit shall be ACO J8P PITLOK® SCEC (SL1) - concrete pit & steel lid - full\* / split\* body as supplied by ACO Pty Ltd. or equal approved.

The pit is fully tested and assessed on behalf of SCEC. SCEC have subsequently endorsed the lids and pits contingent on the use of SCEC (SL3) padlocks to secure the lids.

#### Materials

The pit body shall be manufactured from steel reinforced cement concrete with:

Compressive strength: 40MPa

The nominal clear opening shall be 1,250 x 440mm. Units shall be manufactured with an internal working depth of 910mm.

#### Lid

The pit shall be covered with a SCEC (SL1) approved tamper evident locking steel lid.

#### Installation

The cable pit shall be installed in accordance with the manufacturer's installation instructions and recommendations.

\* delete as applicable

**ACO Limited**  
**New Zealand**  
 Ph: 0800 448 080  
[www.aconz.co.nz](http://www.aconz.co.nz)  
[sales@aconz.co.nz](mailto:sales@aconz.co.nz)

Start Your  
Specification  
Here



© February 2018 ACO Limited. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Limited. pursues a policy of continuous product development and reserves the right to amend specifications without notice.

