




ACO EzyBrixx® - 1200mm x 1200mm – twin walled polypropylene cable pit



H1 (mm)	H2 (mm)	OVERALL HEIGHT (mm)
900	880	950
1050	1030	1100
1200	1180	1250
1350	1330	1400
1500	1480	1550

- Key**
- 1. Clear working dimension at pit opening.
 - 2. Clear working dimension beneath lid components.
 - 3. All dimensions are in mm

Parts Table

Enclosures/Lids		
Descriptions/dimensions	Part No.	Weight (kg)
EzyBrixx 1200mm x 1200mm x (900mm deep) pit	142536	70
EzyBrixx 1200mm x 1200mm x (900mm deep) pit with base	142677	82
EzyBrixx 1200mm x 1200mm x (1050mm deep) pit	142607	82
EzyBrixx 1200mm x 1200mm x (1050mm deep) pit with base	142678	94
EzyBrixx 1200mm x 1200mm x (1200mm deep) pit	142537	94
EzyBrixx 1200mm x 1200mm x (1200mm deep) pit with base	142679	106
EzyBrixx 1200mm x 1200mm x (1350mm deep) pit	142608	106
EzyBrixx 1200mm x 1200mm x (1350mm deep) pit with base	142680	118
EzyBrixx 1200mm x 1200mm x (1500mm deep) pit	142609	118
EzyBrixx 1200mm x 1200mm x (1500mm deep) pit with base	142681	130
EzyBrixx 1200mm x 1200mm (150mm deep) riser (supplied loose)	142584	12
EzyBrixx 1200mm x 1200mm steel (2 part) bolt locking lid - Class B	142577	148
EzyBrixx 1200mm x 1200mm steel (2 part) bolt locking lid - Class D	142496	185

ACO CABLEMATE

ACO EzyBrixx® - 1200mm x 1200mm – twin walled polypropylene cable pit

Accessories

Descriptions	Part No.
EzyBrixx Cable support (each)	142567
EzyBrixx Ladder	POA
Universal lifting key	84306
4m eye to eye lifting slings (set of 4)	142565
Holesaw EzyBrixx: tungsten grit 30mm system - Short Hex	142760
Holesaw EzyBrixx: tungsten grit 65mm system - Short Hex	142761
Holesaw EzyBrixx: tungsten grit 70mm system - Short Hex	142762
Holesaw EzyBrixx: tungsten grit 90mm system - Short Hex	142763
Holesaw EzyBrixx: tungsten grit 120mm system - Short Hex	142764
Holesaw EzyBrixx: tungsten grit 160mm system - Short Hex	142765
Holesaw EzyBrixx: tungsten grit 30mm system -Short SDS	142766
Holesaw EzyBrixx: tungsten grit 65mm system -Short SDS	142767
Holesaw EzyBrixx: tungsten grit 70mm system - Short SDS	142768
Holesaw EzyBrixx: tungsten grit 90mm system - Short SDS	142769
Holesaw EzyBrixx: tungsten grit 120mm system - Short SDS	142770
Holesaw EzyBrixx: tungsten grit 160mm system - Short SDS	142771
Holesaw EzyBrixx: pilot key - 200mm long	142772
Holesaw EzyBrixx: pilot key - 40mm long drift key	142773
Short SDS adaptor	142774
Short HEX adaptor	142775
Long HEX adaptor	142776
Long SDS adaptor	142777
Universal Plug	84625

Specifications

The cable pit shall be ACO EzyBrixx® - 1200mm x 1200mm (clear opening)

- with/without* base
- with/without* 150mm riser
- complete with a bolt lockable Class B/D* steel lid (AS 3996)

The cable pit shall have an overall depth of 900mm/1050mm/1200mm/1350mm/1500mm* or increments created by the 150mm riser, specify _____

The pit body shall be manufactured from modular rigid (twin wall) polypropylene components comprising an interlocking wedge system configured in 150mm high stacking units.

The pit is to be supplied assembled and installed in accordance with the manufacturer’s installations.

* delete as applicable

ACO Limited
New Zealand
Ph: 0800 448 080
www.aconz.co.nz
sales@aconz.co.nz

Start Your
Specification
Here



© October 2020 ACO Limited. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer’s responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Limited pursues a policy of continuous product development and reserves the right to amend specifications without notice.

