



Type 99 polymer concrete cable pit

Cable pit



Optional riser - each riser adds up to 300mm height



ACO CABLEMATE

Type 99 polymer concrete cable pit

Cable pit and riser

Description	Part No	Depth mm	Weight kg
Type 99 polymer concrete pit	75489	582	135.4
Accessories			
Type 99 polymer concrete riser (adds 300mm to pit depth)	75500	350	70.2

Compatible lids and access covers

Description	Part No	Weight kg cover ² total
Polymer concrete 2-part lid (AS 3996 Cl A) - Blank ^{1 3}	75525	29 62
Polymer concrete 2-part lid (AS 3996 Cl A) - Communications ^{1 3}	75532	29 62
Polymer concrete 2-part lid (AS 3996 Cl A) - Electricity ^{1 3}	75541	29 62
Steel 2-part lid (AS 3996 Cl B) ^{1 4}	79920	20 45
Steel 2-part lid (AS 3996 Cl C) ^{1 4}	custom	- -
Steel PowerLok 2-part lid (AS 3996 Cl B) ^{1 4}	79930	25 45
Steel PowerLok 2-part lid (AS 3996 Cl C) ^{1 4}	custom	- -
Steel Urbanfil recessed cover (AS 3996 Cl B) ¹	81645	31 40
Steel Pavermate recessed cover (AS 3996 Cl B) ¹	81992	35 45
Ductile iron Rhinocast recessed cover (AS 3996 Cl B) ¹	85093	86 115
Ductile iron Rhinocast solid top 2-part cover (AS 3996 Cl B) ¹	89953	48 149
Ductile iron Rhinocast recessed cover (AS 3996 Cl D) ¹	89093	136 199
Ductile iron Rhinocast solid top 2-part cover (AS 3996 Cl D) ¹	89955	80 244
Ductile iron Rhinocast recessed 2-part cover (AS 3996 Cl G) ¹	87568	145 380

1. Refer to ACO Cablemate literature for details

2. Lifting weight - kg

3. Lid dimension: 935 x 935 x 50 (mm)

4. Lid dimension: 935 x 935 x 48 (mm)

Specifications

General

The cable pit shall be ACO Cablemate Type 99 with lid/access cover* (see below) as manufactured by ACO Limited or equal approved.

Materials

The pit/riser bodies shall be manufactured from polyester polymer concrete with:

Electrical resistivity 1 x 10⁸ Ω/sq
Compressive strength: 96MPa
Flexural strength: 27MPa
Water absorption 0.07%
Frost proof
Salt proof
Dilute acid and alkali resistant
Surface burn characteristics of the material shall comply with UL 723

The nominal clear opening shall be 855mm x 855mm. Units shall be manufactured with a clear depth of 510mm.

Optional riser

Additional height can be added using one or two polymer concrete riser units - each riser adds up to 300mm height.

Lid/Access cover

The pit shall be covered with a polymer concrete lid*, steel/PowerLok lid*, Urbanfil/Pavermate access cover*, Rhinocast access cover* - see table for compatible options.

Installation

The cable pit shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as applicable

ACO Limited
New Zealand
Ph: 0800 448 080
www.aconz.co.nz
info@aconz.co.nz

Start Your
Specification
Here



SPEC INFO
ACO

© July 2017 ACO Limited. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Limited pursues a policy of continuous product development and reserves the right to amend specifications without notice.