


Type 55 polyethylene cable pit**Cable pit****Key**

- ① Clear working dimension at pit base
- ② Clear working dimension at pit opening
- ③ Clear working dimension beneath rebate

ACO CABLEMATE

Type 55 polyethylene cable pit

Cable pit and riser

Description	Part No	Depth mm	Weight kg
Type 55 polyethylene pit	76253	510	8

Compatible lids and access covers

Description	Part No	Weight kg cover ²	total
Polymer concrete lid (AS 3996 CI A) - Blank ^{1 3}	76279	19	19
Polymer concrete lid (AS 3996 CI A) - Communications ^{1 3}	76285	19	19
Polymer concrete lid (AS 3996 CI A) - Electricity ^{1 3}	76297	19	19
Steel lid (AS 3996 CI B) ^{1 4}	75520	13	13
Steel lid (AS 3996 CI C) ^{1 4}	custom	-	-
Steel PowerLok lid (AS 3996 CI B) ^{1 4}	75530	17	17
Steel PowerLok lid (AS 3996 CI C) ^{1 4}	custom	-	-
Steel Urbanfil recessed cover (AS 3996 CI B) ¹	81565	15	22
Steel Pavermate recessed cover (AS 3996 CI B) ¹	81948	18	24
Ductile iron Rhinocast recessed cover (AS 3996 CI B) ¹	85045	36	60
Ductile iron Rhinocast solid top cover (AS 3996 CI B) ¹	85222	33	63

1. Refer to ACO Cablemate literature for details

2. Lifting weight - kg

3. Lid dimension: 540 x 540 x 50 (mm)

4. Lid dimension: 542 x 542 x 48 (mm)

Specifications

General

The cable pit shall be ACO Limited Type 55 with lid/access cover* (see below) as manufactured by ACO Limited. or equal approved.

Materials

The pit body shall be manufactured from polyethylene with:

Electrical resistivity $1 \times 10^{16} \Omega/\text{sq}$
 Flexural strength: 15MPa
 Water absorption 0.31%
 Frost proof
 Salt proof
 Dilute acid and alkali resistant
 Surface burn characteristics of the material shall comply with UL 723
 IP ratings up to IP4X (AS 60529) - enclosure protection against ingress

Polyethylene moulded pits feature a ribbed construction for strength and durability. The nominal clear opening shall be 445mm x 445mm. Units shall be manufactured with a clear depth of 450mm.

Lid/Access cover

The pit shall be covered with a polymer concrete lid*, steel lid*, PowerLok lid*, Urbanfil/Pavermate access cover*, Rhinocast access cover* - see table opposite for compatible options.

Installation

The cable pit shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as applicable

ACO Limited
 New Zealand
 Ph: 0800 448 080
 www.aconz.co.nz
 info@aconz.co.nz

Start Your
 Specification
 Here



© September 2017 ACO Limited. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Limited. pursues a policy of continuous product development and reserves the right to amend specifications without notice.

SPEC INFO
 ACO